


# TWN4 MultiTech Nano LEGIC 63 M

Miniature RFID module (LF/HF/NFC/BLE) for external 50 Ohm antenna



CO version (SMT mounting)  
Top view



CO version (SMT mounting)  
Rear view

With the TWN4 MultiTech Nano family, ELATEC offers extremely compact RFID modules that are also fully compliant with the TWN4 technology. Their miniature size and low energy consumption give the option to integrate them in smaller battery-powered consumer devices, like tablet PCs, POS terminals or mobile payment systems. Furthermore, their components are mounted on one side only, which facilitates easy placement on the main circuit board. These devices are the ideal solution in case of particular restrictions during the installation (space limitations, metal surrounding the reader antenna, etc.).

Key features of the TWN4 MultiTech Nano LEGIC 63 M RFID module include compact dimensions and two mounting options (Surface Mounting or Through Hole Technology) for an easy integration into almost all mobile and battery-operated applications, as well as the possibility to read more than 60 RFID technologies from low (LF) and high (HF) frequency bands, including NFC, depending on the external antenna/mother board connected to the module. Furthermore, the module is also equipped with an integrated BLE module and the LEGIC frontend chip SM-6300 (optionally, SM-6300init) that supports LEGIC Connect.

#### Special features:

- + Easy integration thanks to a compact design and components mounted only on one side
- + Integrated BLE module and LEGIC frontend chip SM-6300 or SM-6300init with LEGIC Connect support
- + Supports segment initialization function (LEGIC SM-6300init frontend only)
- + Supports connection of external ISO 7816 compatible SAM cards
- + Powerful SDK for writing apps which are executed directly on the reader
- + Firmware update in the field possible
- + On-board 18 kB flash storage, e.g. for storing user accessible non-volatile data
- + Supports transparent data exchange with RFID media
- + Development board and I/O Extender for interface testing on request



Elevator



EV Chargers



Access



Shop POS



Fitness  
Equipment



Ticket POS



PC Log-on



Document  
Management



Driver ID



Vending



Parking



Gaming



Locker Locks



Time  
Attendance



Industrial  
PC


## TECHNICAL DATA

FREQUENCIES	125 kHz (LF) / 13.56 MHz (HF) / 2.4 GHz (BLE)																
ANTENNAS	Externally, 50 Ohm for 13.56 MHz – 490 µH ± 5% for 125 kHz																
DIMENSIONS (L X W X H)	C0 version: approx. 31.00 x 17.80 x 2.70 mm / 1.22 x 0.70 x 0.11 inch C1 version: approx. 31.00 x 17.80 x 8.11 mm / 1.22 x 0.70 x 0.32 inch																
POWER	Direct power supply: 3.3 V ± 5% On-board voltage regulator: 4.3 V – 5.5 V ES1/PS2 classified power source according to IEC 62368-1, short-circuit current < 8 A																
CURRENT CONSUMPTION	RF field on: 160 mA typically / Sleep: 500 µA typ. / Cyclic operation: 130 mA typ.																
TEMPERATURE RANGE	Operating: -25 °C up to +80 °C (-13 °F up to +176 °F) Storage: -40 °C up to +85 °C (-40 °F up to +185 °F)																
RELATIVE HUMIDITY	5% to 95% non-condensing																
OPERATING MODES (USB)	USB keyboard emulation – USB virtual COM port – CCID / PC/SC 2.01																
BLUETOOTH LOW ENERGY	BLE version 5.0 (upgradable) LEGIC Connect on demand																
MTBF	500,000 hours																
WEIGHT	Approx. 8 g / 0.28 oz																
SUPPORTED OPTIONS AND TRANSPONDERS	Depending on the firmware version and installed options, ELATEC readers and modules can support a wide range of RFID technologies. Please refer to the relevant ELATEC transponder matrix (available at <a href="http://www.elatec-rfid.com/int/transponder-technology">www.elatec-rfid.com/int/transponder-technology</a> ) for more information about the available options and RFID technologies supported by the product.																
OS SUPPORT	Windows 7 (32-/64-bit) and higher versions, Linux, Android <sup>1)</sup> , iOS <sup>1)</sup> , MAC OS X <sup>1)</sup>																
PERIPHERAL INTERFACES	USB, 2 x TTL serial (logic level 3.3 V, CMOS 5 V tolerant), I <sup>2</sup> C, SPI, 8 GPIOs, Clock/Data, Wiegand D0/D1																
TRANSMISSION SPEED	Host: USB Full speed (12 Mbit/s), TTL serial: up to 115,200 baud, HF Air: up to 848 kbit/s, BLE Air: up to 1 Mbit/s																
CERTIFICATION NAME	TWN4 MultiTech Nano LEGIC 63 M																
CERTIFICATIONS	Non-exhaustive list <sup>2)</sup> : CE/RED, REACH and RoHS-III compliant																
ORDER CODES	<p><b>C0 version (SMT)</b></p> <table> <tr> <td>T4NM-D5C0</td> <td>Standard reader module</td> </tr> <tr> <td>T4NM-D5C0-P</td> <td>Reader module with P option</td> </tr> <tr> <td>T4NM-D5C0-5</td> <td>Standard reader module with LEGIC SM-6300init</td> </tr> <tr> <td>T4NM-D5C0-5P</td> <td>Reader module with P option and LEGIC SM-6300init</td> </tr> </table> <p><b>C1 version (THT)</b></p> <table> <tr> <td>T4NM-D5C1</td> <td>Standard reader module</td> </tr> <tr> <td>T4NM-D5C1-P</td> <td>Reader module with P option</td> </tr> <tr> <td>T4NM-D5C1-5</td> <td>Standard reader module with LEGIC SM-6300init</td> </tr> <tr> <td>T4NM-D5C1-5P</td> <td>Reader module with P option and LEGIC SM-6300init</td> </tr> </table>	T4NM-D5C0	Standard reader module	T4NM-D5C0-P	Reader module with P option	T4NM-D5C0-5	Standard reader module with LEGIC SM-6300init	T4NM-D5C0-5P	Reader module with P option and LEGIC SM-6300init	T4NM-D5C1	Standard reader module	T4NM-D5C1-P	Reader module with P option	T4NM-D5C1-5	Standard reader module with LEGIC SM-6300init	T4NM-D5C1-5P	Reader module with P option and LEGIC SM-6300init
T4NM-D5C0	Standard reader module																
T4NM-D5C0-P	Reader module with P option																
T4NM-D5C0-5	Standard reader module with LEGIC SM-6300init																
T4NM-D5C0-5P	Reader module with P option and LEGIC SM-6300init																
T4NM-D5C1	Standard reader module																
T4NM-D5C1-P	Reader module with P option																
T4NM-D5C1-5	Standard reader module with LEGIC SM-6300init																
T4NM-D5C1-5P	Reader module with P option and LEGIC SM-6300init																

<sup>1)</sup>On request

<sup>2)</sup>The product has been certified for use in many countries and regions. Contact your Sales representative for detailed information about all certifications and approvals granted to the product.

## TECHNICAL DRAWINGS



### ELATEC GmbH

Zeppelinstr. 1  
82178 Puchheim  
Germany  
P +49 89 552 9961 0  
F +49 89 552 9961 129  
E-Mail: info-rfid@elatec.com  
Website: elatec.com

### ELATEC Systems GmbH

Schwieberdinger Str. 44  
71636 Ludwigsburg  
Germany  
P +49 7141 309736 0  
E-Mail: info-rfid@elatec.com  
Website: elatec.com

### ELATEC Inc.

1995 SW Martin Hwy  
Palm City • FL 34990  
USA  
P +1 772 210 2263  
F +1 772 382 3749  
E-Mail: americas-info@elatec.com  
Website: elatec.com

### ELATEC Technology (Shenzhen) LLC

918, Main Building, Tian An Cyber Times  
Tower, No. 6, Tairan Fourth Road, Tian 'an  
Community, Shatou Neighborhood  
Futian District • Shenzhen • China  
P/F +86 755 2394 6014  
E-Mail: apac-info@elatec.com  
Website: elatec.com

ELATEC reserves the right to change any information or data in this document without prior notice. ELATEC declines all responsibility for the use of this product with any other specification but the one mentioned above. Any additional requirement for a specific customer application has to be validated by the customer themselves at their own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names used in this document are registered trademarks of their respective owners.